

TECHNICAL DATA

PLS 5R KIT, 5-Point Red Laser Kit



Key features

- Accuracy: $\leq 1/8$ in at 30 ft. (≤ 3 mm @ 10 m)
- Red laser beam
- Point laser direction: 90° up, down, left, right, forward
- Durable pendulum lock platform.
- IP54 rating to limit dust and water entry for years of operation on the job site.

Product overview: PLS 5R KIT, 5-Point Red Laser Kit

The new PLS 5R red laser levels offer the durability and precision you expect from PLS, a Fluke Company. Our new laser level platform offers a pendulum lock platform for safe transport and tilt mode functionality. The fast settling, self-leveling pendulum gives you accurate point and reference lines almost instantly.

- The PLS 5 is a self-leveling, five-point red laser level (plumb, level, and square horizontal and vertical points) equipped for multiple applications.
- Includes the PLS Pendulum Target for easy transfer of points to the floor during square alignment.
- Kit includes floor stand and L-bracket for fast, easy overhang and centerline measurements.

Specifications: PLS 5R KIT, 5-Point Red Laser Kit

PLS 5R	
Battery	3 x AA Alkaline IEC LR6

PLS 5R		
Battery Life, Continuous Use	Red	≥ 30 hours
	Green	≥ 9 hours
Point Laser Direction	90° up, down, left, right, forward	
Working Range	≤ 30 m (100 ft.)	
Accuracy	≤ 3 mm @ 10 m (≤ 1/8 in at 30 ft.)	
Laser Leveling	System	Automatic, Pendulum
	Range	4 °
Point Laser Diameter	≤ 4 mm at 5 m	
Temperature	Operating	-10 °C to 50 °C (14 °F to 122 °F)
	Storage	15 cm x 9 cm x 3 cm (6 in x 3.6 in x 1.3 in)
	With Batteries	-18 °C to 50 °C (-0.4 °F to 122 °F)
	Without Batteries	-20 °C to 70 °C (-13 °F to 158 °F)
Relative Humidity	0 % to 90 % (0 °C to 35 °C)	
	0 % to 75 % (35 °C to 40 °C)	
	0 % to 45 % (40 °C to 50 °C)	
Size (H x W x L)	116 mm x 64 mm x 104 mm (4.6 in x 2.5 in x 4.1 in)	
Weight	~0.6 kg (1.3 lb.)	
Safety	IEC 61010-1: Pollution Degree 2	
Laser	IEC 60825-1:2014 Class 2	
Light Source	Semiconductor laser diode	
Max Output Power	< 1 mW	
Wavelength	Red	635 nm ± 5 nm
	Green	525 nm ± 5 nm

Electromagnetic Compatibility (EMC)

International
Korea (KCC)
USA (FCC)

Fluke. *Keeping your world up and running.®*

Fluke Europe B.V.
P.O. Box 1186
5602 BD Eindhoven
The Netherlands
www.fluke.com/en

©2022 Fluke Corporation. All rights reserved.
Data subject to alteration without notice.
02/2022

For more information call:
In Middle East/Africa
+31 (0)40 267 5100

**Modification of this document is not permitted
without written permission from Fluke Corporation.**