

TECHNICAL DATA

Fluke Calibration P5513 Pneumatic Comparison Test Pump



Key features

- High pressure pneumatic operation
- Screw press for fine pressure adjustments
- High quality needle valves for fine control
- Test port adapters which require no PTFE tape or wrenches
- Sturdy carrying case with lid

Product overview: Fluke Calibration P5513 Pneumatic Comparison Test Pump

Pressure range 0 to 3,000 psi (210 bar)

This pneumatic comparison test pump is designed for testing pressure measuring instruments against master test instruments. This cost effective instrument provides precise control for important calibration requirements and include many features found in our popular line of pneumatic deadweight testers.

*Note --- Unit requires pressure source (i.e. nitrogen bottle) for operation.

Specifications: Fluke Calibration P5513 Pneumatic Comparison Test Pump

Specifications	
Pressure Range	0 to 3,000 psi (210 bar)
Instrument Size (W x D x H)	17.5 x 12 x 8.5 in (440 x 300 x 215 mm)
Instrument Weight	17 lbs (8 kg)
Test Port Adapters	2 sets, 1/8, 1/4, 3/8 and 1/2 NPT or BSP
Gas Supply Connection	1/4 NPT female

Ordering information



Fluke P5513

Fluke Calibration P5513 Pneumatic Comparison Test Pump
Pressure range 0 to 3,000 psi (210 bar)

Fluke. *Keeping your world up and running.®*

Fluke Europe B.V.

P.O. Box 1186
5602 BD Eindhoven
The Netherlands
www.fluke.com/en

©2022 Fluke Corporation. All rights reserved.
Data subject to alteration without notice.
02/2022

For more information call:

In Middle East/Africa
+31 (0)40 267 5100

**Modification of this document is not permitted
without written permission from Fluke Corporation.**