

RCD TESTER

Digital RCD Tester



MODEL 5406A

- Custom microprocessor controlled for highest accuracy and reliability.
- 3 LEDs for checking correct wiring status.
- 0 and 180 degree phase angle switch permits quick tests and consistent readings.
- Digital read-out of tripping time.
- Test DC sensitive breakers.
- Constant current source circuitry ensures that a fluctuating mains voltage does not affect the accuracy of readings.
- Large custom digital display readout.
- Visual indication of reversed phase and neutral wiring at socket.
- Designed to IP54 Rating.
- Complies with IEC61557.

● Specifications

| | |
|--------------------------|--|
| Rated Tripping Current | 10/20/30/200/300/500mA |
| Fault Condition Settings | ×1/2, ×1, ×5, DC, AUTO RAMP |
| Trip Current Duration | 1000ms, 200ms (×5) |
| Trip Time Accuracy | 0.6%rdg±4dgt |
| Operating Voltage | 230V+10%-15% (195V-253V) 50Hz |
| Safety Standard | IEC61557-1, -6 IEC61010-1 CAT. III 300V Pollution Degree 2 IEC61010-2-031 |
| IP Rating | IEC60529-IP54 |
| Dimensions | 184(L)×167(W)×89(D)mm |
| Weight | 800g approx. |
| Accessories | Molded plug test leads Pouch for test leads Shoulder Strap Instruction Manual |
| Optional | 7121 Distribution board test leads |