

Model 1011



EMC & LVD  
EN: 61326  
EN: 61010-1  
EN: 61010-02-032  
EN: 61010-02-033



The tester is a designed and very practical tester that can easily read the correct pin configuration of 10 Base -T cable(Category 5), 10 Base-2 cable (coax), RJ45/RJ11 modular cables, 356A, TIA-568A/568B and Token Ring cable by comparing one transmitting end to the corresponding receiving end. With the remote kit it can test cables installed far away either on wall plate or patch panel. It is easy to verify the cable continuity, open, short and cross-connect. It is affordable, so you can benefit the most.

- Test the correct pin configuration of 10 Base-T 10 Base-2 Thin Ethernet cable, RJ45/RJ11 modular cables 356A, TIA-568A/568B and Token Ring cable etc.
- With remote kit it can remotely test cables up to 300 m away either on the wall plate or patch panel.
- Test the ground wire
- Measures DC/AC Voltage, DC/AC Current, Resistance, Continuity & diode

**Specifications**

Function	Max Range	Basic Accuracy
Voltage DC	600V	±0.5%
Voltage AC	600V	±1.2%
Current DC	200mA	±1.5%
Current AC	200mA	±2.0%
Resistance	20MΩ	±0.8%
Continuity Test	Beep if less than 100Ω	

Size(HxWxD): 162mm x 74.5mm x 44mm

Weight: 308g

Accessories: 9V battery and Two "AAA" batteries, remote terminator, holster, cables, test leads, gift box with carrying case.



LA-1015 2 in 1 Cable Identifier & DMM



EMC & LVD  
EN: 50081-1, 50082-1  
EN: 61010-1, EN: 61010-02-032  
EN: 61010-02-033



Model 1015

LA-1015 is a transmitter/receiver device which enables one to instantly match up ends of individual cores at either end of a multi-core cable. With the remote kit it can test cables installed far away either on wall plate or patch panel. DMM function make it easy to measure DC/ AC voltage, DC/AC current, Resistance, continuity & diode.

**Specifications**

Function	Max Range	Basic Accuracy
Voltage DC	600V	±0.5%
Voltage AC	600V	±1.2%
Current DC	200mA	±1.5%
Current AC	200mA	±2.0%
Resistance	20MΩ	±0.8%
Continuity Test	Beep if less than 100Ω	

**Transmitter**

Display	Two blue LED lamps	
Alligators	17 Croc Clips - Red x 16, Black x 1	
Cable resistance	10K Ohm max	

**Receiver**

Display	Two digit Red LED Display	
Alligators	2 Croc Clips - Red x 1, Black x 1	

Size(HxWxD): 162mm x 74.5mm x 44mm

Weight: 308g

Accessories: 9V battery and Two "AAA" batteries, remote terminator, holster, cables, test leads, gift box with carrying case.



EMC & LVD  
EN: 61326  
EN: 61010-1  
EN: 61010-02-032  
EN: 61010-02-033



Model 1016

LA-1016 is a satellite finder with scale display and digital multimeter (DMM). It is very good design. Connect a coaxial cable from the LNB/LNBF to the "TOLNB" connection on Satellite Finder. Connect the cable from your satellite receiver to the "TOREC" input on the Satellite Finder. DMM function make it easy to measure DC/AC voltage, DC/AC current, Resistance, continuity & diode.

**Specifications**

Function	Max Range	Basic Accuracy
Voltage DC	600V	±0.5%
Voltage AC	600V	±1.2%
Current DC	200mA	±1.5%
Current AC	200mA	±2.0%
Resistance	20MΩ	±0.8%
Continuity Test	Beep if less than 100Ω	

Size(HxWxD): 162mm x 74.5mm x 44mm

Weight: 308g

**Accessories:**

9V battery & Two "AAA" batteries, remote terminator and gift box with carrying case.



LA-1017 Solar Power Meter & DMM

**Features**

- Sunlight measurement up to 1999w/m<sup>2</sup> or 634BTU/(ft<sup>2</sup>\*h)
- High accuracy and rapid response
- Data HOLD function to hold measurement values
- Unit and sign display for easy reading
- Measuring unit selection among w/m<sup>2</sup> and BTU/(ft<sup>2</sup>\*h)
- Manual scale selection
- Direct reading with no adjustments needed
- Maximum and minimum values
- Low battery indication

**Specifications**

Function	Max Range	Basic Accuracy
Voltage DC	600V	±0.5%
Voltage AC	600V	±1.2%
Current DC	200mA	±1.5%
Current AC	200mA	±2.0%
Resistance	20MΩ	±0.8%
Continuity Test	Beep if less than 100Ω	

**Solar Power Meter**

Display	3-1/2 digits LCD with maximum reading 1999.	
Range	1999W/m <sup>2</sup> , 634BTU/(ft <sup>2</sup> *h)	
Resolution	1W/m <sup>2</sup> , 1BTU/(ft <sup>2</sup> *h).	
Accuracy	Typically within ±10W/m <sup>2</sup> [±3BTU/(ft <sup>2</sup> *h)] or ±5%	
Sampling time	Approx 0.25 second.	

Size(HxWxD): 162mm x 74.5mm x 44mm

Weight: 308g

**Accessories:**

9V battery & Two "AAA" batteries, remote terminator and gift box with carrying case.



EMC & LVD  
EN: 61326  
EN: 61010-1  
EN: 61010-02-032  
EN: 61010-02-033



Model 1017